

REVISIONS REV. DESCRIPTION DATE

PART NUMBER DIM. A PS301A-0131GG-P .125" PS301A-0132GG-P .180" PS301A-0133GG-P .215"

INITIAL RELEASE 9/21/2020

В .290





1. INSULATOR MATERIAL: GLASS FILLED POLYESTER

2. FLAMABILITY RATING: UL94V-O

3. OPERATING TEMP: -55C TO +125C

4. ACCEPTS -.015-.021 DIAMETER PIN

5. SHELL MATERIAL: BRASS ALLOY C36000, 1/2 HARD

6. SHELL PLATING 10 μ MIN. OVER NICKEL, 100 μ MIN

7. CONTACT MATERIAL: BeCu

8. CONTACT PLATING: 10μ MIN. OVER NICKEL, 100μ MIN

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±.1 ANGULAR: MACH±.1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN	AM	09/21/20
	CHECKED	SB	09/21/20
	ENG APPR.		
	MFG APPR.		
INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.		
	COMMENTS:		

DO NOT SCALE DRAWING

301 PGA SOCKET 20X20 GRID

Adapters-Plus Inc. Ph: 209-839-0200 web: www.adapt-plus.com

SIZE DWG. NO. SCALE: 1:1

PS301A-013XGG-P

WEIGHT: SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL

IS PROHIBITED.

THE INFORMATION CONTAINED IN THIS

IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ADAPTERS-PLUS

ADAPTERS-PLUS INC. ANY REPRODUCTION

DRAWING IS THE SOLE PROPERTY OF

REV

В