

# PA44-PP-PP-xx Data Sheet


## 44 pin PLCC socket/44 pin PLCC plug

### Supported Device/Footprints

These adapter are PLCC socket extenders. They accept 44 pin PLCC devices and plugs into 44 pin PLCC production sockets. Test points are provided near the edges of the circuit board.

Mfgr	Socket		Device	Plug	
	Device	Package		Package	Package
Many	44 pin	PLCC	44 pin	PLCC	

### Adapter Dimensions



PA44-PP-PP

### Adapter Construction

The adapter is a single soldered together assembly. The adapters described by this datasheet and their sub-assemblies are:

Adapter	Board	Plug length
PA44-PP-PP	44PL	21.6 mm (0.850")
PA44-PP-PP-29.2	44PL	29.2 mm (1.150")

All versions have a PLCC production socket soldered to the top side.

### Test Points

These adapters offer Test Points. The Test Points are rows of plate-thru-holes (PTH) along the 4 edges of the adapter.

Grabbers may be used to hook onto the holes.

Alternately, 0.050" pitch 11 pin strips can be soldered into the holes and connections made to the strip's pins. A right angle strip should be considered for easier access to the pins.

### Adapter Wiring

This adapter is wired 1 to 1. Pin 1 of the socket is connected to pin 1 of the plug. Pin 2 to pin 2 and so on around the adapter.



**Adapters-Plus Inc.**

P.O. BOX 900  
Tracy, Ca 95378  
ph.209-839-0200  
fax.209-839-0235  
email: sales@adapt-plus.com

www.adapt-plus.com

PA44-PP-PP-xx Data Sheet  
Doc: 44PPPP.DOC  
Rev 07/06/00  
Page 1 of 1